



# WEET Technology Company Limited

## General Purpose Rectifiers

**S1A THRU S1M**


**VOLTAGE RANGE** 50 to 1000 Volts  
**CURRENT** 1.0 Ampere

**FEATURES**

- Glass passivated chip:46mil
- Low forward voltage drop
- Low leakage current
- High forward surge capability
- High temperature soldering:  
260°C/10S at terminals
- Component in accordance to  
ROHS 2002/95/1 and WEEE 2002/96/EC

**MECHANICAL DATA**

- Case: JEDEC SOD-123FL mold plastic  
Body over glass passivated chip
- Terminals:Solder plated, solderable per  
J-STD-002B and JESD22-B102D
- Polarity: Laser band denote cathode band



**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	S1A	S1B	S1D	S1G	S1J	S1K	S1M	UNITS	
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	Volts	
Maximum RMS Voltage	$V_{RMS}$	35	70	140	280	420	560	700	Volts	
Maximum DC Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	Volts	
Maximum Average Forward Rectified Current	$I_{(AV)}$	1.0							Amps	
Peak Forward Surge Current 8.3mS single half sine-wave superimposed on rated load (JEDEC method)	$I_{FSM}$	30							Amps	
Maximum Instantaneous Forward Voltage at 1.0A	$V_F$	1.1							Volts	
Maximum DC Reverse Current at Rated DC Blocking Voltage	$T_A = 25^\circ C$	$I_R$							5.0	$\mu A$
	$T_A = 125^\circ C$									
Typical Junction Capacitance (NOTE 1)	$C_j$	15							pF	
Typical Thermal Resistance (NOTE 2)	$R_{\theta JA}$	60							$^\circ C/W$	
Operating and Storage Temperature Range	$T_J, T_{STG}$	-55 to +150							$^\circ C$	

**Notes:**  
 1.Measured at 1.0MHz and applied reverse voltage of 4.0 Volts.  
 2.Thermal Resistance from Junction to Ambient at.  $5.0 \times 5.0mm^2$  copper pad areas.



# WEE Technology Company Limited

## General Purpose Rectifiers

S1A THRU S1M

VOLTAGE RANGE 50 to 1000 Volts  
CURRENT 1.0 Ampere

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS





FIG.5-TYPICAL JUNCTION CAPACITANCE



Note: Specifications are subject to change without notice. For more detail and update, please visit our website.